

Continuous Motion Side Sealer Shrink Wrap Machine

Model: V'M2

The VM Pack Continuous Motion Side Sealer Shrink Wrapping Machine stands out with its innovative design and servo motion technology, offering uninterrupted high speed packaging in demanding production environments. The continuous motion sealing bar works in perfect synchronization with the product flow, ensuring consistent and high quality sealing throughout the packaging process.

At VM Pack, we not only manufacture standard machines but also offer customized shrink packaging solutions specifically designed to meet your industry's needs. Contact us for detailed information on technical specifications, integration options, and customized solutions.



| Feature | Description |
|--|--|
| Continuous Motion Sealing bar | High speed continuous motion sealing bar ensures precise and reliable sealing. |
| Servo Motor Control | Enables precise and high speed cutting and sealing operations with servo driven control systems. |
| Color Touch screen Control Panel | User friendly interface allows for quick and easy adjustment of the machine settings. |
| Operating Modes | Sensor, measurement, and print mark(optional) modes adapt to various production needs. |
| Automatic Product Length Detection | Automatically detects product length for seamless packaging. |
| Motorized Width and Height Adjustment | Automatically adjusts to product dimensions. |

| | |
|-------------------------------------|--|
| Front-Rear Package Spacing | Adjustable in millimeters. |
| Recipe System | Allows for the saving of product parameters to enable quick recall and repeated use. |
| Product Counter | Counts the total number of packages produced during operation. |
| Motorized Film Waste Winding | Automatic winding system precisely collects shrink film waste generated during the packaging process. Speed is adjustable via drive control. |
| Motorized Film Unwinding | Automatically unwinds the shrink film from the roll during operation. Speed is adjustable via drive control. |
| Machine Material | The machine body is manufactured from steel construction and protected with electrostatic powder coating. |
| Warranty | 1-year warranty, with 5-year spare parts availability. |
| CE Compliance | The machine is equipped with mechanical and electrical safety measures in accordance with CE directives. |
| Max. Product Dimensions | Width: 410 mm, Length: unlimited, Height: 200 mm |
| Max. Speed | 35 meters/minute |
| Packaging Material | 7–19 micron (POF), 35–50 micron (PE) |
| Max. Roll Width | 650 mm |
| Air Pressure | 6 Bar |
| Voltage | 380V, 50/60Hz |